

Hahn
KT-EV
KT-SN
KT-SV



Application area For PVC U profiles Housing Public building	✓ ✓ x	✓ ✓ x	✓ ✓ x
Material Extruded aluminum profiles	✓	✓	✓
Size Width Height	 102.5 mm 97 mm	85 mm 97 mm	85 mm 97 mm
Weight capacity / resistance	120 kg	80 kg	80 kg
Maintenance free	✓	✓	✓
Color options RAL-colors	✓	✓	✓
Fastening High degree of pre-mounted parts KT-Fix Direct Fastening/standard screws/self drilling screws For left hand and right hand doors No interruption of gasket Additional lateral fixing in upstand	✓ ✓ ✓/✓ ✓ ✓ x	✓ x ✓/✓ ✓ ✓ ✓	✓ x ✓/✓ ✓ ✓ x
Upstand ranges 15–20 mm 16.5–21.5 mm 18–23 mm 20–25 mm 22–27 mm	✓ ✓ ✓ x ✓	✓ ✓ ✓ x ✓	✓ ✓ ✓ x ✓
Special version for narrow and very narrow frames	✓	x	✓
Regulation Regulation by only 1 person In 6 directions without removing sash Without modification of esthetics Horizontal regulation Vertical regulation Sealing compression adjustment continuously ±2,5 mm/+0,5 mm additional in upstand range	✓ ✓ ✓ continuously ±5 mm continuously +3/-2 mm ✓/x	✓ ✓ ✓ continuously ±5 mm continuously +3/-2 mm ✓/x	✓ ✓ ✓ continuously ±5 mm continuously +3/-2 mm ✓/x
Certification CE-Certification according to EN 1935:2002 SKG	✓ 2 stars	✓ 2 stars	✓ x